

WALL & ROOF WRAP

DESCRIPTION:

Residential & commercial wall
& roof insulation.

Heavy Duty Wall Wrap

- Duty: Heavy
- Vapour Barrier: High
- Emittance: Reflective
- Water Barrier: High
- Flammability Index: Low
- R. value: Winter R 1.0
Summer R 1.1

Metal Roofing

- Duty: Heavy
- Vapour Barrier: High
- Emittance: Reflective
- Water Barrier: High
- Flammability Index: Low
- R. value: Winter R 1.1
Summer R 1.5

PROPERTIES:

WALL WRAP

Flammability Index < 5	< 5
Tensile Strength Machine Direction (kN/M)	Min. 12.5
Tensile Strength Lateral Direction (kN/M)	Min. 7.5
Edge Tear Resistance Machine Direction (N)	Min. 80
Edge Tear Resistance Lateral Direction (N)	Min. 80
Water Vapour Transmission Rate (Ng/Ns)	Max 2
Emittance of Reflective Face	Max 0.05

METAL ROOFING

SIZES:

Wall Wrap

- 1350mm x 20 metre
- 1350mm x 60 metre

Roof Sarking

- 1350mm x 60 metre



Flammability Index < 5	< 5
Tensile Strength Machine Direction (kN/M)	Min. 12.5
Tensile Strength Lateral Direction (kN/M)	Min. 7.5
Edge Tear Resistance Machine Direction (N)	Min. 80
Edge Tear Resistance Lateral Direction (N)	Min. 80
Water Vapour Transmission Rate (Ng/Ns)	Max 2
Emittance of Reflective Face	Max 0.05