

SUPERCOURSE 500 DAMPCOURSE

DESCRIPTION:

Supercourse Dampcourse is a black, 0.5mm thick, flexible, high impact resistant, embossed polyethylene film, for use as a concealed moisture proof barrier in brickwork and window construction.

USES:

- Concealed flashing placed across the cavity of a masonry wall to prevent against rising damp
- Flashing around windows
- Other construction applications

FEATURES & BENEFITS:

- Economical to use in comparison to traditional damp-proof courses such as bitumen coated aluminum
- Acid, alkali and moisture resistant
- Not affected by lime or cement
- Highly resistant to salt damp conditions
- Australian made

<u>SIZES</u>	<u>CODE 30M</u>	<u>Roll</u>	<u>CODE 50M</u>	<u>Roll</u>
110mm x 500um	2222b	18	2222B	12
150mm x 500um	2222c	12	2222C	9
230mm x 500um	2222d	8	2222D	6
300mm x 500um	2222e	6	2222E	4
380mm x 500um	2222f	4	2222F	3
450mm x 500um	2222g	4	2222G	3
600mm x 500um	2222h	2	2222H	2
900mm x 500um	-		2222I	

PACKAGING:

24 cartons per pallet

STANDARDS COMPLIANCE:

Complies with Australian standards AS2904-1995.
 Thickness tested in accordance with AS/NZS 4347.9
 Impact resistance tested in accordance with AS/NZS 4347.6
 Puncture & moisture resistant



Tampala Pty Ltd trading as BIY Construction Supplies
 23-25 Clyde Street, Wingfield SA 5013
 Phone: 08 8347 0444 www.biy.com.au
 ABN 47 008 016 082

Product Disclaimer: Tampala Pty. Ltd. trading as B.I.Y. Construction Supplies products are based on practical experience and their quality standards are warranted as specified. As B.I.Y. Construction Supplies have no control over the purpose for which the products are used or their method of application, no warranty can be given as to the results obtained under varying conditions of usage. The performance of B.I.Y. Construction Supplies products is dependent on the strict adherence to the instructions issued and carried out by competent applicators.