

HYDROCHLORIC ACID 33%

DESCRIPTION:

Hydrochloric Acid is a solution of hydrogen chloride in water that is used as a pool pH adjuster and surface preparation treatment.

HOW TO USE:

- Brick Cleaning & Etching - remove lumps of cement with a scraper and wash bricks thoroughly with water. Mix 1 part Hydrochloric Acid to 10 parts water. Apply Acids solution with a broad brush and rinse off with water once chemical reaction (frothing) has ended.
- pH adjuster for pool water - add 100ml per 40,000 litres of water to lower pH by 0.1 on the pH scale ie 7.9 to 7.8. Run pool pump for at least an hour after adding acid.

SAFETY:

Wear suitable protective clothing, gloves and eye/face protection when using this product. Always add acid to water (never add water to acid).

FEATURES & BENEFITS:

- Colourless liquid with a very sharp, biting odor (do not inhale)
- Widely used in mining, building and pool industries

TYPICAL CHARACTERISTICS:

- Specific Gravity: 1.18
- Boiling Point: 91-98°C
- pH: <1

RANGE OF SIZES	CODE
5 litre (4 per carton)	1078B
20 litre (32 per pallet)	1078A



Updated Feb 2025

Tampala Pty Ltd trading as BIY Construction Supplies
23-27 Clyde Street, Wingfield SA 5013
ABN 47 008 016 082

Phone 08 8347 0444
www.biy.com.au
sales@biy.com.au